

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 11/13/24



Issue date 06/11/15

* 1 Identification

- **Product identifier**
- **Trade name:** Eosin Stain Solution
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information
- **Product description** Eosin stain solution prepared from Biologic Stain Commission certified dye
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dermatologic Lab & Supply, Inc.
4001 E Plano Pkwy, Ste 100
Plano, TX 75074
Voice: (800) 831-6273 or (712) 323-3269
Fax: (800) 320-9612 or (712) 323-1156
www.delasco.com
- **Emergency telephone number:** Chemtrec 800-424-9300

*

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

STOT SE 2 H371-H335 May cause damage to organs. May cause respiratory irritation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

• **Signal word** Danger

• **Hazard-determining components of labeling:**

Ethyl alcohol
Isopropyl alcohol
Methanol

• **Hazard statements**

Highly flammable liquid and vapor.
Causes skin and eye irritation. May cause damage to organs.
May cause respiratory irritation.

• **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
If on skin: Wash with plenty of water.
If exposed or concerned: Call a poison center/doctor.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Classification system:** NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

• **HMIS-ratings (scale 0 - 4)**



Health = *2
Fire = 3
Reactivity = 0

• **Hazard(s) not otherwise classified (HNOC):** None known

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

* 3 Composition/information on ingredients

7732-18-5	Water, distilled water, deionized water	15-35%
-----------	---	--------

• **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

• **Dangerous Components:**

CAS: 64-17-5 RTECS: KQ 6300000	Ethyl alcohol ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%
CAS: 67-56-1 RTECS: PC 1400000	Methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; ⚠ Acute Tox. 3, H311; ⚠ Acute Tox. 3, H331; ⚠ STOT SE 1, H370	2-12%
CAS: 67-63-0 RTECS: NT 8050000	Isopropyl alcohol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2-12%

* 4 First-aid measures

• **Description of first aid measures**

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
In case of unconsciousness, place patient securely on side position for transportation.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

• **After eye contact:** Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

Do not induce vomiting without medical advice. Drink copious amounts of water and provide fresh air. Immediately call a doctor.

• **Information for doctor:**

• **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

• **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

* 5 Fire-fighting measures

• **Extinguishing media**

• **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **Special hazards arising from the substance or mixture** No further relevant information available.

• **Advice for firefighters** Use water spray to cool unopened containers.

• **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

* 6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

Avoid contact with skin, eyes and clothing.
Keep people at a distance and stay upwind.
Keep away from ignition sources Do not inhale gases / fumes / aerosols Treat any fumes as toxic. Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation. Dispose of the collected material according to regulations.

- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Keep away from heat and direct sunlight.
Avoid contact with skin, eyes and clothing
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.
Do not cut, grind or weld on container that contains or contained product.
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

Store away from acid chlorides, acid anhydrides, strong oxidizing agents, Alkali metals, strong reducing agents, strong acids, Ammonia, Aluminum and Halogenated compounds.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

• **Components with occupational exposure limits:**

64-17-5 Ethyl alcohol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm Upper Respiratory Tract irritation

67-56-1 Methanol

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI, headache, nausea, dizziness, eye damage

67-63-0 Isopropyl alcohol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

• **Ingredients with biological limit values:**

67-56-1 Methanol

BEI	15 mg/L urine end of shift Methanol (background, nonspecific)
-----	--

67-63-0 Isopropyl alcohol

BEI	40 mg/L urine end of shift at end of workweek Acetone (background, nonspecific)
-----	--

• **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

• **Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin. ·

Breathing equipment:

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution



Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles ·

Body protection:



Protective work clothing

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information · Appearance:**

Form: Liquid

Color: Colorless

· **Odor:** Alcohol

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 78 °C (172 °F)

· **Flash point:** 13 °C (55 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 425 °C (797 °F)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
 - Lower:** 0.0 Vol %
 - Upper:** 15.0 Vol %
- **Vapor pressure @ 20 °C (68 °F):** 59 hPa (44 mm Hg)
- **Density:**
 - Relative density** Not determined.
 - Vapor density** Not determined.
 - Evaporation rate** Not determined.
- **Solubility in / Miscibility with**
 - Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 80.0 %
 - Water:** 19.7 %
 - VOC content:** 80.0 %
 - Solids content:** 0.3 %
- **Other information** No further relevant information available.

* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flame and ignition sources.
- **Incompatible materials:**

Acid chlorides, acid anhydrides, strong oxidizing agents, Alkali metals, strong reducing agents, strong acids , Ammonia, Aluminum and Halogenated compounds.
- **Hazardous decomposition products:** Carbon Oxides and Nitrogen Oxides (NOx).

* 11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**
 - **LD/LC50 values that are relevant for classification:**
- | |
|-----------------------|
| 64-17-5 Ethyl alcohol |
|-----------------------|

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

Oral	LD50	7060 mg/kg (rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h LC50/96 hours	20000 mg/l (rat) 12900-15300 mg/l (Trout)
67-56-1 Methanol		
Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4 h LC50/96 hours	128.2 mg/l (rat) 15400 mg/l (Trout)
67-63-0 Isopropyl alcohol		
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h LC50/96 hours	30 mg/l (rat) 9640 mg/l (Pimephales)

- **Primary irritant effect:** · **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:**
Irritating effect. Causes serious eye irritation.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

67-63-0	Isopropyl alcohol	Page 9 of 33
15086-94-9	Eosin Y	Safety Data Sheet (SDS)
• NTP (National Toxicology Program) Standard 29 CFR 1910.1200(g) and GHS Rev 03. Issue date 08/17/10 None of the ingredients are listed.		
• OSHA (Occupational Safety & Health Administration) None of the ingredients are listed.		

12 Ecological information

• **Toxicity**

• **Aquatic toxicity:**

64-17-5 Ethyl alcohol

EC50 34900 mg/l (daphnia)

67-56-1 Methanol

EC50 22000 mg/l (Green algae)
10000 mg/l (daphnia)

67-63-0 Isopropyl alcohol

EC50 6851 mg/l (Green algae)
5102 mg/l (Water flea)

• **Persistence and degradability** No further relevant information available.

• **Behavior in environmental systems:**

• **Bioaccumulative potential** No further relevant information available.

• **Mobility in soil** No further relevant information available.

• **Additional ecological information:** • **General notes:** Not known to be hazardous to water. • **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

• **Waste treatment methods**

• **Recommendation:**

Observe all federal, state and local environmental regulations when disposing of this material.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

• **Recommended cleansing agent:** Water, if necessary with cleansing agents.

Safety Data Sheet (SDS)




OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

* 14 Transport information

- UN-Number	UN1993
- DOT, ADR, IMDG, IATA	UN1993
- UN proper shipping name	Flammable liquids, n.o.s. (Ethanol, Methanol)
- DOT	UN1993 Flammable liquids, n.o.s. (Ethanol, Methanol)
- ADR	FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), METHANOL)
- IMDG	FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANOL)
- IATA	
- Transport hazard class(es)	
- DOT	
	
- Class	3 Flammable liquids
- Label	3
- ADR	
	
- Class	3 (F1) Flammable liquids
- Label	3
- IMDG, IATA	
	
- Class	3 Flammable liquids
- Label	3
- Packing group	
- DOT, ADR, IMDG, IATA	II
- Environmental hazards:	Not applicable.
- Special precautions for user	Warning: Flammable liquids
- Danger code (Kemler):	33
- EMS Number:	F-E, S-E
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

- **ADR**
- **Excepted quantities (EQ)**

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

Page 11/13

- **IMDG**
- **Limited quantities (LQO)** SHA HazCom Standard 5.29 CFR 1910.1200(g) and GHS Rev 03.
- **Excepted quantities (EQ)**

Issue date 06/11/15

Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
UN1993, Flammable liquids, n.o.s. (Ethanol, Methanol), 3, II

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

- **UN "Model Regulation":**

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

• Section 355 (extremely hazardous substances):

None of the ingredients are listed.

• Section 313 (Specific toxic chemical listings):

67-56-1 Methanol

67-63-0 Isopropyl alcohol

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

• California Proposition 65

• Chemicals known to cause cancer:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

• Chemicals known to cause developmental toxicity:

64-17-5 Ethyl alcohol

67-56-1 Methanol

• Carcinogenic categories

• EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH)

64-17-5 Ethyl alcohol

A3

67-63-0 Isopropyl alcohol

A4

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

• Hazard pictograms



GHS02 GHS07 GHS08

- **Signal word** Danger

• Hazard-determining components of labeling:

Ethyl alcohol
Isopropyl alcohol
Methanol

- **Hazard statements**

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

Highly flammable liquid and vapor.

Causes skin and eye irritation. May cause damage to organs.

May cause respiratory irritation. ·

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

If on skin: Wash with plenty of water.

IF exposed or concerned: Call a poison center/doctor.

Take off contaminated clothing and wash it before reuse.

Store locked up.










Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know

CAS: 64-17-5 RTECS: KQ 6300000	Ethyl alcohol  Flam. Liq. 2, H225;  Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%
CAS: 7732-18-5	Water, distilled water, deionized water	15-35%
CAS: 67-63-0 RTECS: NT 8050000	Isopropyl alcohol  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	2-12%
CAS: 67-56-1 RTECS: PC 1400000	Methanol  Flam. Liq. 2, H225;  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;  STOT SE 1, H370	2-12%
CAS: 15086-94-9	Eosin Y	□ 2.5%
CAS: 64-19-7 RTECS: AF 1225000	Acetic Acid  Flam. Liq. 3, H226;  Skin Corr. 1A, H314	□ 2.5%
All ingredients are listed.		

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 11/13/24

Trade name: Eosin Stain Solution

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• **Date of preparation / last revision**

06/11/15 – 11/13/2024

• **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

• *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106