

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 09/25/18



Issue date 06/11/15

* 1 Identification

- **Product identifier**
- **Trade name: Skin Marking Ink**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information
- **Product description** Skin marking ink
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dermatologic Lab & Supply, Inc.
608 13th Ave.
Council Bluffs, IA USA 51501-6401
Voice: (800) 831-6273 or (712) 323-3269
Fax: (800) 320-9612 or (712) 323-1156
www.delasco.com
- **Emergency telephone number:** Chemtrec 800-424-9300

*

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
STOT SE 3 H335 May cause respiratory irritation.Eye Irrit. 2B H320 Causes eye irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**

Ethyl alcohol
Isopropyl alcohol
Methanol

- **Hazard statements**

Highly flammable liquid and vapor.
Causes skin and eye irritation.
Suspected of causing cancer.
May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
Store locked up.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 3
Reactivity = 0

· **Hazard(s) not otherwise classified (HNOC):** None known

* 3 Composition/information on ingredients

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous Components:**

CAS: 64-17-5 RTECS: KQ 6300000	Ethyl alcohol ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	25-50%
CAS: 67-56-1 RTECS: PC 1400000	Methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; ⚠ Acute Tox. 3, H311; ⚠ Acute Tox. 3, H331; ⚠ STOT SE 1, H370	□ 2.5%
CAS: 67-63-0 RTECS: NT 8050000	Isopropyl alcohol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	□ 2.5%
CAS: 548-62-9	C.I. Basic Violet 3 ⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302	□ 2.5%

* 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

· **After eye contact:** Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting without medical advice. Drink copious amounts of water and provide fresh air. Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters** Use water spray to cool unopened containers.
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Avoid contact with skin, eyes and clothing.
Keep people at a distance and stay upwind.
Keep away from ignition sources Do not inhale gases / fumes / aerosols Treat any fumes as toxic. Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation. Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Avoid contact with skin, eyes and clothing
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Do not cut, grind or weld on container that contains or contained product.
Keep ignition sources away - Do not smoke.
Protect from heat.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

Store away from acid chlorides, acid anhydrides, strong oxidizing agents, Alkali metals, strong reducing agents, strong acids, Ammonia, Aluminum and Halogenated compounds.

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

64-17-5 Ethyl alcohol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm
Upper Respiratory Tract irritation

67-56-1 Methanol

PEL Long-term value: 260 mg/m³, 200 ppm

REL Short-term value: 325 mg/m³, 250 ppm
Long-term value: 260 mg/m³, 200 ppm
Skin

TLV Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm
Skin; BEI, headache, nausea, dizziness, eye damage

67-63-0 Isopropyl alcohol

PEL Long-term value: 980 mg/m³, 400 ppm

REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm
BEI

- **Ingredients with biological limit values:**

67-56-1 Methanol

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

BEI	15 mg/L urine end of shift Methanol (background, nonspecific)
67-63-0 Isopropyl alcohol	
BEI	40 mg/L urine end of shift at end of workweek Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**



Suitable respiratory protective device recommended.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: **Skin Marking Ink**



Protective work clothing

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information · Appearance:**

- **Form:** Liquid
- **Color:** Colorless
- **Odor:** Alcohol
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.

· **Change in condition**

- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:** 78 °C (172 °F)
- **Flash point:** 13 °C (55 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 425 °C (797 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

- **Lower:** 0.0 Vol %
- **Upper:** 15.0 Vol %
- **Vapor pressure @ 20 °C (68 °F):** 59 hPa (44 mm Hg)
- **Density @ 20 °C (68 °F):** 0.898 g/cm³ (7.494 lbs/gal)
- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

- **Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**

- **Dynamic:** Not determined.
- **Kinematic:** Not determined.

Solvent content:

- **Organic solvents:** 47.5 %
- **Water:** 51.5 %
- **VOC content:** 47.5 %
- **Solids content:** 0.5 %

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

- **Other information** No further relevant information available.

* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flame and ignition sources.
- **Incompatible materials:**
Acid chlorides, acid anhydrides, strong oxidizing agents, Alkali metals, strong reducing agents, strong acids , Ammonia, Aluminum and Halogenated compounds.
- **Hazardous decomposition products:** Carbon Oxides, Nitrogen Oxides (NOx) and Hydrochloric acid gas.

* 11 Toxicological information

- **Information on toxicological effects** ·

Acute toxicity:

- **LD/LC50 values that are relevant for classification:**

64-17-5 Ethyl alcohol		
Oral	LD50	7060 mg/kg (rat) Remarks: Lungs, Thorax, or Respiration: Other changes. Carcinogenicity - Mouse - Oral Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease. Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Heart - Irregularities - Based on Human Evidence Central nervous system - Breathing difficulties - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence
Inhalative	LC50/4 h LC50/96 hours	20000 mg/l (rat) 12900-15300 mg/l (Trout)
67-56-1 Methanol		
Oral	LD50	5628 mg/kg (rat)
Dermal	LD50	15800 mg/kg (rabbit)
Inhalative	LC50/4 h LC50/96 hours	128.2 mg/l (rat) 15400 mg/l (Trout)
67-63-0 Isopropyl alcohol		
Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h LC50/96 hours	30 mg/l (rat) 9640 mg/l (Pimephales)
548-62-9 C.I. Basic Violet 3		
Oral	LD50	420 mg/kg (rat) 150 mg/kg (rabbit)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

- **Primary irritant effect:** · **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:**
Irritating effect. Causes serious eye irritation.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

67-63-0	Isopropyl alcohol	3
---------	-------------------	---

- **NTP (National Toxicology Program)**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

* 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

64-17-5 Ethyl alcohol

EC50	34900 mg/l (daphnia)
------	----------------------

67-56-1 Methanol

EC50	22000 mg/l (Green algae)
	10000 mg/l (daphnia)

67-63-0 Isopropyl alcohol

EC50	6851 mg/l (Green algae)
	5102 mg/l (Water flea)

548-62-9 C.I. Basic Violet 3

EC50	0.35 mg/l (Water flea)
------	------------------------

- **Persistence and degradability** No further relevant information available.

Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

- **General notes:** Harmful to aquatic organisms ·

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods ·**




Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

* 14 Transport information

- **UN-Number** UN1993
 - **DOT, ADR, IMDG, IATA** Flammable liquids, n.o.s. (Ethanol, Methanol)
 - **UN proper shipping name** Flammable liquids, n.o.s. (Ethanol, Methanol)
 - **DOT** UN1993 Flammable liquids, n.o.s. (Ethanol, Methanol)
 - **ADR** FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), METHANOL)
 - **IMDG** FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANOL)
 - **IATA**
 - **Transport hazard class(es)**
 - **DOT**
- 
- **Class** 3 Flammable liquids
 - **Label** 3
-
- **ADR**
- 
- **Class** 3 (F1) Flammable liquids
 - **Label** 3
-
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<hr/>	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1993, Flammable liquids, n.o.s. (Ethanol, Methanol), 3, II

* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· Section 355 (extremely hazardous substances):
None of the ingredients are listed.
· Section 313 (Specific toxic chemical listings):
67-56-1 Methanol
67-63-0 Isopropyl alcohol
· TSCA (Toxic Substances Control Act):
All ingredients are listed.
· California Proposition 65
· Chemicals known to cause cancer:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
· Chemicals known to cause developmental toxicity:
64-17-5 Ethyl alcohol
67-56-1 Methanol

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

· Carcinogenic categories

· EPA (Environmental Protection Agency)	
None of the ingredients are listed.	
· TLV (Threshold Limit Value established by ACGIH)	
64-17-5 Ethyl alcohol	A3
67-63-0 Isopropyl alcohol	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients are listed.	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Ethyl alcohol
Isopropyl alcohol
Methanol

· Hazard statements

Highly flammable liquid and vapor.
Causes skin and eye irritation.
Suspected of causing cancer.
May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: Skin Marking Ink

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.













Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

(Contd. on page 13)

· **State Right to Know**

CAS: 7732-18-5	Water, distilled water, deionized water	40-60%
CAS: 64-17-5 RTECS: KQ 6300000	Ethyl alcohol  Flam. Liq. 2, H225;  Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	25-50%
CAS: 67-63-0 RTECS: NT 8050000	Isopropyl alcohol  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	□ 2.5%
CAS: 67-56-1 RTECS: PC 1400000	Methanol  Flam. Liq. 2, H225;  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;  STOT SE 1, H370	□ 2.5%
CAS: 548-62-9	C.I. Basic Violet 3  Carc. 2, H351;  Eye Dam. 1, H318;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Acute Tox. 4, H302	□ 2.5%
CAS: 633-03-4 RTECS: BP 6825000	Brilliant Green  Acute Tox. 4, H302	□ 2.5%
All ingredients are listed.		

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision**

09/24/18 - 09/25/18

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/11/15

Reviewed on 09/25/18

Trade name: **Skin Marking Ink**

IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 3: Acute toxicity, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· * **Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106